

INDFLOC 905

Polymer for Retention and Drainage

Application

INDFLOC 905 is high efficiency poly electrolyte, specially designed for Retention and Drainage in the Paper Making process. The application includes retaining the fines fillers and other paper making furnish components. In broad spectrum for all liquid separation applications INDFLOC-905 is an excellent Polymer. This is very effective on broad pH range. INDFLOC-905 is very effective in controlling the hydrodynamics of the stock at forming zone.

Product Data

- | | |
|---|---------------------|
| • Appearance | Free Flowing Powder |
| • Ionic Character (Anionic) | Low |
| • pH of 0.1 % Solution | 6.0 – 7.5 |
| • Bulk Viscosity of 0.1 % Solution (cps) | 30 - 80 |

Benefits

- Rapid Dissolution
- Improves the run ability of machine
- High Drainage rate
- Highly efficient
- Improved white water clarity
- Excellent in retaining Ash

Features

- Easy to prepare solution and apply
- Effective at low dosages
- Completely miscible with water

Direction for Use

INDFLOC 905 may be unloaded manually or pumped directly into the dilution tank from the container. Prepare stock solution (0.5 to 1.0 % w/v) of the poly electrolyte using process/Filtered water. Prepare feed solution by diluting the stock solution directly or by on-line using water. Chemicals can be dosed by dosing equipment. Dosing system is recommended by Ion Exchange (India) Limited based on the requirement of the clients.

Handling

Do not store the material in open. Keep the container tightly closed when not in use. These products exhibit very low order of oral toxicity. No special care is required in handling these products. The area where the polymer is prepared should be kept dry and clean always as the polymer spillage might cause a slippery surface.

Ion Exchange LLC

46722, Fremont Blvd., Fremont, CA – 94538, USA.

Phone: 408 649 5639 Fax: 408 649 5658 Email: info@ionexchangeglobal.com

Website: www.ionexchangeglobal.com